

Arithmetic Calculations

- Avoid using **multiplications** and **divisions** whenever possible. These complex mathematic calculations need a lot processing power and (what's even worse) a huge library to be compiled at all.
- If you need to multiply with and divide through even numbers like 2, 4, 8, 16, 32 ... you can make use of the bitshifting operators "»" and "«"

```
unsigned char c;
c = 12 >> 1; // c is 6 (division through 2)
c = 12 >> 2; // c is 3 (division through 4)
c = 12 << 1; // c is 24 (multiplication by 2)
c = 12 << 2; // c is 48 (multiplication by 4)
c = 1023 >> 3; // c is 127 (10bit to 7bit ;)
```

- There's an excellent thread in the forum that discusses bitoperations:
<http://www.midibox.org/forum/index.php?topic=6981.0>
- If this is not enough, you could search for ASM optimized custom functions. You'll find some in code examples of TK, the [ACSensorizer](#) and a lot of PIC-Specialized Webpages - or of course the forum.
- If that still is not enough or you have no time and a lot of processing power / space available on your PIC, you can include the **libsdcc library**:

if multiplications, divisions, pointer operations, etc. are used in the .c code, the linker may fail due to missing functions, which are part of the libsdcc.lib library. The common library for pic16 derivatives is not compatible to MIOS, therefore I've created a special one which can be downloaded from [here](#). Read the README.txt file for further details. [TK on the C-Page](#)

Bitfields, Unions & Structs

- Avoid using huge int- or char-arrays when you just need to store some ON/OFF values. Use a bitfield instead

```
// define the bitfield
typedef union {
    struct {
        unsigned ALL:8; // by calling something.ALL, you get the whole
        bitfield as 8-bit number
    };
    struct {
        unsigned led1:1; // by calling something.led1 you get one bit-
        state (1 or 0)
        unsigned led2:1;
        unsigned led3:1;
        unsigned led4:1;
        unsigned free:4;
    };
};
```

```
};  
} something_t;  
  
// declare var  
something_t something;  
  
// set bits  
something.led1 = 1;  
something.led3 = ;  
  
// get number  
mynum = something.ALL;
```

Due to an SDCC restriction, bitfields are limited to 8 bits max

C Functions

- MIOS*_SRSet and _SRGet Functions refer to the pins in [Little-Endian](#) order, so for example:

MIOS_DOUT_SRSet(1, 00000001) Will set the 1st pin (aka Pin 0).... or

MIOS_DOUT_SRSet(1, 01000000) Will set the 7th pin (aka Pin 6)

C Optimizations

- [How to mix C and ASM](#)
- [Compiled C Code Size](#)

C Variables

- Declaring a [variable](#) as type 'const' will cause the [compiler](#) to store the variable in the PIC's program [flash memory](#), not the [SRAM](#).
- Adding the keyword '[volatile](#)' to a [variable](#) is a good idea when this variable can be changed or altered outside the sourcefile that declared this variable.
- Always use 'unsigned' if you are sure you don't need negative values. As it's not clear how C treats a 'char' (signed: -128 to 127; unsigned: 0 to 255), it's better to be clear here.

SDCC Bugs/Workarounds

Some of these bugs have first been described in a [german thread in the forum](#).

Array Access

Sometimes the transfer of an array between modules does not work properly, e.g. file 1:

```
unsigned char MIDIValues[8];
```

file 2:

```
MIOS_MIDI_TxBufferPut(MIDIValues[1]);
```

Instead, you need to do something like

```
unsigned char value = MIDIValues[1]; //explicit temp variable  
MIOS_MIDI_TxBufferPut(value);
```

Large Arrays

Arrays with more than 256 elements will produce compile (in fact linker) errors:

```
unsigned char myArray[256]; // will work  
unsigned char myArray[257]; // will not be linked!  
  
unsigned char myArray[64][4]; // will work  
unsigned char myArray[64][5]; // will not be linked!
```

This is due to the fact that the PIC's RAM has been segmented into 256-byte banks in the linker script, and an array's contents may not span across more than one bank.

The linker script can be modified to work around the 256-byte limitation by creating larger banks, as per the [Linker Script](#) and [Application Code](#) tips on the 4620 page.

Thanks to Thomas for [testing some workarounds with multiple single-dimensional arrays](#). These methods would be recommended if possible.

Bit Copy Operations

There is potential trouble with bit copy operations (See [this posting](#)). Instead of

```
app_flags.SRAM_CARD_STATUS = PORTEbits.RE2;
```

you should use

```
if( PORTEbits.RE2 ){  
    app_flags.SRAM_CARD_STATUS = 1;  
}else{  
    app_flags.SRAM_CARD_STATUS = ;  
}
```

It is less elegant, but it works safely.

Parenthesis

Always use parenthesis around expressions like

```
myarray[a+b];
```

instead use

```
myarray[(a+b)];
```

Preprocessor #ifs

Avoid `#ifdef` and `#if` preprocessor-statements wrapped around declarations and function prototypes. Even if the preprocessor's `#if` statement is true (eg defined as '1'), any access to it's vars and functions from outside these wrapped statements produce a compile-warning:

```
#define TEST 1  
  
#if TEST  
    unsigned char testvar;  
#endif /* TEST */  
  
void testfunction(void) {  
    unsigned char c = testvar + 1; // access to testvar produces compiler  
    error!
```

}

Zero Compare

Avoid comparisons of unsigned char with , e.g.

```
unsigned char i;
for (i = ; i < ; i++) {
    // body
}
```

0 could be a constant that was defined using #define, e.g. the number of motorized faders. But you have no motorized faders... The main problem consists in the fact that your code depends on what else is done around the comparison or in the body. This provokes completely erratic behaviour.

Stack Size

TK says:

The stack boundaries are defined in the file header of mios_wrapper/mios_wrapper.asm:

```
; the upper boundary of the stacks are defined here
; customize the values for your needs
#ifndef STACK_HEAD
#define STACK_HEAD 0x37f
#endif

#ifndef STACK_IRQ_HEAD
#define STACK_IRQ_HEAD 0x33f
#endif
```

The default setup is 64 bytes for main tasks, 64 bytes for interrupt tasks. (stack pointer is counted down, there is no collision control to save runtime)

Since a PIC18F4620 has enough memory, you could use two 256 bytes stacks located at the upper RAM pages:

```
#define STACK_HEAD 0xeef
#define STACK_IRQ_HEAD 0xdff
```

this should relax the situation.

Note that the appr. memory area (0xd00-0xeef) should be reserved in the projekt.lkr file Note that stacks greater than 256 bytes will not work with SDCC at present.

Last
update:
2008/02/11 c_tips_and_tricks_for_pic_programming http://wiki.midibox.org/doku.php?id=c_tips_and_tricks_for_pic_programming&rev=1197972476
13:40

From:
<http://wiki.midibox.org/> - **MIDIbox**

Permanent link:
http://wiki.midibox.org/doku.php?id=c_tips_and_tricks_for_pic_programming&rev=1197972476 

Last update: **2008/02/11 13:40**